

Slip Proof NZ Ltd - Deck Tread

In most cases, Deck Tread can be fixed using either screws or glue only. Slip Proof NZ recommends glueing and screwing for the following substrates:

- Unseasoned timber (newly laid) as can be susceptible to expansion and contraction
- Warped or deteriorated timber surfaces
- Degraded or crumbling concrete surfaces

Note:

- Deck Tread can be cut on site using a drop saw with a cut off disc.
- Deck Tread can be screwed with self-drilling, self-countersinking screws or cap screws
- Ensure substrate is clean and dry before commencing installation

Recommended Fasteners:

- Anzor- CSK SQ P-B T 17 RIB 8G X 1-1/4 304, Self-drilling self-countersinking screws (available from Slip Proof)

Installation to Timber substrate: Decking, Boardwalks, Ramps, etc

- Wipe back of FRP Deck Tread with Surface Activator (available at Slip Proof) or Acetone to remove contaminants.
- Place a bead of adhesive on underside of the Deck Tread
- Place Deck Tread in desired location and stick down.
- Starting from one end, screw Deck Tread to the substrate down the middle of the entire length of Deck Tread , with maximum screw spacing of 200mm for 50mm wide Deck Tread and a maximum spacing of 500mm for the 90mm Deck Tread.
- Walk over entire length of Deck Tread to ensure full contact has been achieved with the substrate.

Installation to Concrete Substrate:

IF THE CONCRETE SURFACE IS IN POOR CONDITION, WE RECOMMEND GLUEING AND SCREWING. If screwing only, please ignore steps 1-3 below

- Starting at one end, predrill holes every 500mm along the middle of the top of the Deck Tread
 - Place Deck Tread in situ and mark through the holes using a permanent marker
 - Drill holes where marked, clean away drillings and install concrete plugs
1. Wipe back of FRP Deck Tread with Surface Activator or Acetone to remove contaminants.
 2. Place a bead of adhesive on underside of Deck Tread
 3. Walk over entire length of Deck Tread to ensure adhesive makes full contact with both substrates
 4. Screw down to concrete surface

Disclaimer

- Please note, these are recommendations only and should be used as a guide
- Slip Proof NZ deck treads adhere to multiple industry standard Adhesives. It is up to the installer to determine the suitability of any products that have not been tested by Slip Proof NZ Ltd.
- Slip Proof NZ Ltd will not accept any liability for failures due to installation error or those that aren't a direct Deck Tread product fault.